



- © 2006 The Authors
Journal compilation © 2006 Blackwell Publishing Ltd

ADOPTABLE DRAINAGE NOTES

Specification for the Water Industry 6th Edition.

pointed with resin modified mortar.

connections. Frame depth shall be 150mm.

of a greater depth than 1.0 μm . Mild steel plastic encapsulated double doors may be provided in accordance with 2.0m in depth.

10. Hot dipped galvanized mild steel ladders should be installed in
Type 1A manholes

between 70 degrees and 90 degrees across the full width of vertical clearance in excess of 300mm.

13. Red coloured plastic marker tape at least 150mm wide shall be

non-metallic pipes.

15. All PLASTIC pipework is to be Thermoplastic Structured Wall pipe

PipeWork 10 BS 5911: Part 100

to be fitted with a temporary debris screen to prevent debris entering

19. All connections to adoptable manholes from private building

1985.

[illegible]

23. where pipes are beneath drives or parking courts and less than 500mm depth to eoffit the nine bedding shall be minimum 100mm

forming, lumps of clay over 100mm, unbedded, frozen material and vegetable matter.

26. Brickwork to chambers shall be Class B Engineering to BS3921.

Additional documents added to the record	25.02.16	B)
Key updated	09.03.16	

REV	DATE	INITIAL
-----	------	---------

NEW YORK

11.7.1

1:350 @ A1 08.01.16

Drawing No.	Revision

Drawing No.	Revision